



# TECHNICAL DATA SHEET

## - SE WINDPROOF FAMILY -

### ITEM SPECIFICATION:

"Eterno Windproof" pedestal are composed of 3 elements:

A cylindrical base element of 205mm diameter with holes for water drainage and n. 4 "guide" lines to facilitate the cutting in case of need.

A screw with variable height from 30mm to 552mm, is equipped with an unscrewing safety lock.

A head with n. 4 spacing tabs of 14mm height and 4mm thickness, easily removable in case of need and a anti slip ribber on the top.

The height adjustment is carried out by our special adjustment key, which acts on the screw independently from both the head and the base.

### PRODUCT RANGE:

#### CHARACTERISTICS:

Adjustable in hightness  
Bi-component material (PP and rubber)  
Regulation key for highness adjustment  
Easy removable tabs

#### RAW MATERIAL:

Polypropylene and rubber (head top finishing)

#### ENVIRONMENTAL IMPACT:

recyclable material - not dangerous

#### APPLICATIONS SURFACES:

On any waterproofing membrane  
On any insulating hard panel  
On any compact and solid surface

#### APPLICATIONS AREA:

Usable with any prefabricated self sustaining element for outdoor flooring, with minimum thickness of 15mm

### GENERAL CHARACTERISTICS & PROPERTIES

	UNIT	VALUE	+/- N°
BASE DIAMETER	mm	205	+/- 1.0
BASE THICKNESS	mm	5	+/- 0.2
HEAD DIAMETER	mm	150	+/- 0.8
SURFACE OF THE BASE	cmq	330	+/- 5
TABS THICKNESS	mm	4	+/- 0.2
TABS HIGHNESS	mm	14	+/- 0.2
SHORE	Shore d	70	+/- 3
SLOPE CORRECTION		%	0-5
FIRE REACTION*	class	UNI EN**	E
LOW T(°C) REACTION	°C		-40
RESISTANCE TO WIND DEPRESSION ***	Pa	700	

\*Tests made by Giordano S.p.A. Institute of Bellaria-Igea Marina (RN)-Italy

\*\*UNI-EN 13501-1:2009

\*\*\*Tests made by Giordano S.p.A. Institute of Bellaria-Igea Marina (RN)-Italy 1Pa ≈ 1Kg/m2

# TECHNICAL DATA SHEET

## - SE WINDPROOF FAMILY -



### PARTICULAR CHARACTERISTICS & PROPERTIES

<b>SE W 0_E440030040</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	30	+/- 1,0
MAX HEIGHTNESS	mm	40	+/- 1,5
WEIGHT	kg	0.27	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	20	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	11.5	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	40
BOXES PER PALLET	45
BOX DIMENSION	46x40x33.5cm
BOX WEIGHT	10.8kg
PALLET	80x120cm

<b>SE W 1_E440039052</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	39.5	+/- 1,0
MAX HEIGHTNESS	mm	52	+/- 1,5
WEIGHT	kg	0.34	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	16	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	11.5	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	30
BOXES PER PALLET	45
BOX DIMENSION	46x40x33.5cm
BOX WEIGHT	10.5kg
PALLET	80x120cm

<b>SE W 2_E440052077</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	52	+/- 1,0
MAX HEIGHTNESS	mm	77	+/- 1,5
WEIGHT	kg	0.425	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	16.5	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	14	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25
BOXES PER PALLET	45
BOX DIMENSION	46x40x33.5cm
BOX WEIGHT	10.8kg
PALLET	80x120cm

<b>SE W 3_E440077122</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	77	+/- 1,0
MAX HEIGHTNESS	mm	122	+/- 1,5
WEIGHT	kg	0.54	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	19.5	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	15	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25
BOXES PER PALLET	30
BOX DIMENSION	39.5x60x38cm
BOX WEIGHT	13.7kg
PALLET	80x120cm

<b>SE W 4_E440122172</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	122	+/- 1,0
MAX HEIGHTNESS	mm	172	+/- 1,5
WEIGHT	kg	0.6	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	21	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	18	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25
BOXES PER PALLET	24
BOX DIMENSION	39.5x60x38cm
BOX WEIGHT	15.3kg
PALLET	80x120cm

<b>SE W 5_E440172217</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	172	+/- 1,0
MAX HEIGHTNESS	mm	217	+/- 1,5
WEIGHT	kg	0.61	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	19	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	15	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25
BOXES PER PALLET	20
BOX DIMENSION	40x62x40cm
BOX WEIGHT	15.5kg
PALLET	80x120cm

# TECHNICAL DATA SHEET

## - SE WINDPROOF FAMILY -



### PARTICULAR CHARACTERISTICS & PROPERTIES

<b>SE W 6_E440142232</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	142	+/- 1,0
MAX HEIGHTNESS	mm	232	+/- 1,5
WEIGHT	kg	0.78	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	16.3	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	11	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE3 + 25 P1
BOXES PER PALLET	30 / 42
BOX DIMENSION	39.5x60x38cm / 29.5x39x39cm
BOX WEIGHT	13.7kg + 5.9kg
PALLET	80x120cm

<b>SE W 7_E440187277</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	187	+/- 1,0
MAX HEIGHTNESS	mm	277	+/- 1,5
WEIGHT	kg	0.84	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	16.4	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	12.3	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE4 + 25 P1
BOXES PER PALLET	24 / 42
BOX DIMENSION	39.5x60x38cm / 29.5x39x39cm
BOX WEIGHT	15.3kg + 5.9kg
PALLET	80x120cm

<b>SE W 8_E440237327</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	237	+/- 1,0
MAX HEIGHTNESS	mm	327	+/- 1,5
WEIGHT	kg	0.85	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	15	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	12.7	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE5 + 25 P1
BOXES PER PALLET	20 / 42
BOX DIMENSION	40x62x40cm / 29.5x39x39cm
BOX WEIGHT	15.5kg + 5.9kg
PALLET	80x120cm

<b>SE W 9_E440207347</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	207	+/- 1,0
MAX HEIGHTNESS	mm	347	+/- 1,5
WEIGHT	kg	1.04	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	15.3	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	11	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE3 + 25 P1(X2)
BOXES PER PALLET	30 / 42
BOX DIMENSION	39.5x60x38cm / 29.5x39x39cm
BOX WEIGHT	13.7kg + 5.9kg(X2)
PALLET	80x120cm

<b>SE W 10_E440252387</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	252	+/- 1,0
MAX HEIGHTNESS	mm	387	+/- 1,5
WEIGHT	kg	1.08	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	15	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	12.30	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE4 + 25 P1(X2)
BOXES PER PALLET	24 / 42
BOX DIMENSION	39.5x60x38cm / 29.5x39x39cm
BOX WEIGHT	15.3kg + 5.9kg(X2)
PALLET	80x120cm

<b>SE W 11_E440302402</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	302	+/- 1,0
MAX HEIGHTNESS	mm	402	+/- 1,5
WEIGHT	kg	1.1	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	15	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	13.8	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE5 + 25 P1(X2)
BOXES PER PALLET	20 / 42
BOX DIMENSION	40x62x40cm / 29.5x39x39cm
BOX WEIGHT	15.5kg + 5.9kg(X2)
PALLET	80x120cm

# TECHNICAL DATA SHEET

## - SE WINDPROOF FAMILY -



### PARTICULAR CHARACTERISTICS & PROPERTIES

<b>SE W 12_E440272457</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	272	+/- 1,0
MAX HEIGHTNESS	mm	457	+/- 1,5
WEIGHT	kg	1.28	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	15.85	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	11.1	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE3 + 25 P1(X3)
BOXES PER PALLET	30 / 42
BOX DIMENSION	39.5x60x38cm / 29.5x39x39cm
BOX WEIGHT	13.7kg + 5.9kg(X3)
PALLET	80x120cm

<b>SE W 13_E440317502</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	317	+/- 1,0
MAX HEIGHTNESS	mm	502	+/- 1,5
WEIGHT	kg	1.31	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	15.2	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	12	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE4 + 25 P1(X3)
BOXES PER PALLET	24 / 42
BOX DIMENSION	39.5x60x38cm / 29.5x39x39cm
BOX WEIGHT	15.3kg + 5.9kg(X3)
PALLET	80x120cm

<b>SE W 14_E440367552</b>	UNIT	VALUE	+/- N°
min HEIGHTNESS	mm	367	+/- 1,0
MAX HEIGHTNESS	mm	552	+/- 1,5
WEIGHT	kg	1.32	+/- 5 %
MAX CENTRAL COMPRESSION LOADING RESISTANCE*	kN	16.1	/
MAX ECCENTRIC COMPRESSION LOADING RESISTANCE*	kN	12	/

<b>PACK/STORAGE</b>	
PIECES PER BOX	25 SE5 + 25 P1(X3)
BOXES PER PALLET	20 / 42
BOX DIMENSION	40x62x40cm / 29.5x39x39cm
BOX WEIGHT	15.5kg + 5.9kg(X3)
PALLET	80x120cm

\*Tests made by Civil and Environmental Department of University of Padova. 1 kN = 98,6 kg

The above data are relevant to current production and may be changed or updated by Eterno Ivica at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Eterno Ivica. All rights reserved.



Eterno Ivica S.r.l. - Via Austria n. 25/E 35127 Padova, Italy  
T +39 049 8530101, T exp. +39 049 8530102, F +39 049 8530111  
eternoivica@eternoivica.com - www.eternoivica.com

