



TECHNICAL DATA SHEET

- NM WINDPROOF FAMILY -



ITEM SPECIFICATION:

NM Windproof pedestal are composed of 3 elements:

A cylindrical base element of 205mm diameter with holes for water drainage and n. 4 "guide" lines to facilitate the cutting in case of need.

A screw with variable height from 30mm to 275mm, is equipped with an unscrewing safety lock.

A head with n. 4 spacing tabs of 14mm height and 4mm thickness, easily removable in case of need and a anti slip ribber on the top.

The height adjustment is carried out by our special adjustment key, which acts on the screw independently from both the head and the base.

PRODUCT RANGE:

CHARACTERISTICS:

Adjustable in height
Bi-component material (PP and rubber)
Regulation key for height adjustment
Easy removable tabs

RAW MATERIAL:

Polypropylene and rubber (head top finishing)

ENVIRONMENTAL IMPACT:

recyclable material - not dangerous

APPLICATIONS SURFACES:

On any waterproofing membrane
On any insulating hard panel
On any compact and solid surface

APPLICATIONS AREA:

Usable with any prefabricated self sustaining element for outdoor flooring, with minimum thickness of 15mm

GENERAL CHARACTERISTICS & PROPERTIES

| | UNIT | VALUE | +/- N° |
|----------------------------|---------|----------|---------|
| BASE DIAMETER | mm | 205 | +/- 1.0 |
| BASE THICKNESS | mm | 2 | +/- 0.2 |
| HEAD DIAMETER | mm | 150 | +/- 0.8 |
| SURFACE OF THE BASE | cmq | 330 | +/- 5 |
| TABS THICKNESS | mm | 4 | +/- 0.2 |
| TABS HIGHNESS | mm | 14 | +/- 0.2 |
| SHORE | Shore d | 70 | +/- 3 |
| SLOPE CORRECTION | | % | 0-5 |
| FIRE REACTION* | class | UNI EN** | E |
| LOW T(°C) REACTION | °C | | -40 |

*Tests made by Giordano S.p.A. Institute of Bellaria-Igea Marina (RN)-Italy

**UNI-EN 13501-1:2009

TECHNICAL DATA SHEET

- NM WINDPROOF FAMILY -



PARTICULAR CHARACTERISTICS & PROPERTIES

| NM W 1_E014030047 | UNIT | VALUE | +/- N° |
|---|------|-------|---------|
| min HEIGHTNESS | mm | 30 | +/- 1,0 |
| MAX HEIGHTNESS | mm | 45 | +/- 1,5 |
| WEIGHT | kg | 0.265 | +/- 5 % |
| MAX CENTRAL COMPRESSION LOADING RESISTANCE* | kN | 31.18 | / |
| MAX ECCENTRIC COMPRESSION LOADING RESISTANCE* | kN | 15.19 | / |

| PACK/STORAGE | |
|---------------------|----------------|
| PIECES PER BOX | 40 |
| BOXES PER PALLET | 33 |
| BOX DIMENSION | 28.5x39.5x60cm |
| BOX WEIGHT | 10.8kg |
| PALLET | 80x120cm |

| NM W 2_E014045077 | UNIT | VALUE | +/- N° |
|---|------|-------|---------|
| min HEIGHTNESS | mm | 45 | +/- 1,0 |
| MAX HEIGHTNESS | mm | 75 | +/- 1,5 |
| WEIGHT | kg | 0.33 | +/- 5 % |
| MAX CENTRAL COMPRESSION LOADING RESISTANCE* | kN | 38.67 | / |
| MAX ECCENTRIC COMPRESSION LOADING RESISTANCE* | kN | 21.48 | / |

| PACK/STORAGE | |
|---------------------|----------------|
| PIECES PER BOX | 30 |
| BOXES PER PALLET | 36 |
| BOX DIMENSION | 28.5x39.5x60cm |
| BOX WEIGHT | 10.2kg |
| PALLET | 80x120cm |

| NM W 3_E014065107 | UNIT | VALUE | +/- N° |
|---|------|-------|---------|
| min HEIGHTNESS | mm | 65 | +/- 1,0 |
| MAX HEIGHTNESS | mm | 105 | +/- 1,5 |
| WEIGHT | kg | 0.341 | +/- 5 % |
| MAX CENTRAL COMPRESSION LOADING RESISTANCE* | kN | 46.53 | / |
| MAX ECCENTRIC COMPRESSION LOADING RESISTANCE* | kN | 26.07 | / |

| PACK/STORAGE | |
|---------------------|------------|
| PIECES PER BOX | 25 |
| BOXES PER PALLET | 34 |
| BOX DIMENSION | 33x40x60cm |
| BOX WEIGHT | 8.9kg |
| PALLET | 80x120cm |

| NM W 4_E014095167 | UNIT | VALUE | +/- N° |
|---|------|-------|---------|
| min HEIGHTNESS | mm | 95 | +/- 1,0 |
| MAX HEIGHTNESS | mm | 165 | +/- 1,5 |
| WEIGHT | kg | 0.48 | +/- 5 % |
| MAX CENTRAL COMPRESSION LOADING RESISTANCE* | kN | 29.57 | / |
| MAX ECCENTRIC COMPRESSION LOADING RESISTANCE* | kN | 16.75 | / |

| PACK/STORAGE | |
|---------------------|--------------|
| PIECES PER BOX | 15 |
| BOXES PER PALLET | 40 |
| BOX DIMENSION | 46x33.5x40cm |
| BOX WEIGHT | 7.5kg |
| PALLET | 80x120cm |

| NM W 5_E014155277 | UNIT | VALUE | +/- N° |
|---|------|-------|---------|
| min HEIGHTNESS | mm | 155 | +/- 1,0 |
| MAX HEIGHTNESS | mm | 275 | +/- 1,5 |
| WEIGHT | kg | 0.61 | +/- 5 % |
| MAX CENTRAL COMPRESSION LOADING RESISTANCE* | kN | 28.60 | / |
| MAX ECCENTRIC COMPRESSION LOADING RESISTANCE* | kN | 18.89 | / |

| PACK/STORAGE | |
|---------------------|--------------|
| PIECES PER BOX | 12 |
| BOXES PER PALLET | 35 |
| BOX DIMENSION | 46x33.5x40cm |
| BOX WEIGHT | 7.6kg |
| PALLET | 80x120cm |

*Tests made by Civil and Environmental Department of University of Padova. 1 kN = 98,6 kg

The above data are relevant to current production and may be changed or updated by Eterno Ivica at any time without notice. Given the many possible uses and the possible interference of external elements, we do not assume responsibility for the results. The buyer is required to establish under their own responsibility the suitability of the product for the intended use. This document is property of Eterno Ivica. All rights reserved.



Eterno Ivica S.r.l. - Via Austria n. 25/E 35127 Padova, Italy
T +39 049 8530101, T exp. +39 049 8530102, F +39 049 8530111
eternoivica@eternoivica.com - www.eternoivica.com

